SAFETY DATA SHEET

AESUB blue

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Trade name

AESUB blue

Unique formula identifier (UFI)

W01J-20JW-J00W-7MGR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Paint

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Scanningspray Vertriebs GmbH
Johann-Strauss-Str. 13
45657 Recklinghausen
Germany
+49 (0)2361 8903 357
info@aesub.com

Contact person

Max Liese

E-mail

liese@aesub.com

Revision

20/10/2026

SDS Version

1.0

1.4. Emergency telephone number

(CCN 994267 / WISAG FMO Cargo Service GmbH &
Co. KG);
24 Hour Emergency Contact Telephone Number (WISAG) - United Kingdom;
Telephone: 44-870-8200418;

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP).

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.
STOT SE 3; H336, May cause drowsiness or dizziness.
Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)
May cause drowsiness or dizziness. (H336)
Harmful to aquatic life with long lasting effects. (H412)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)
Read label before use. (P103)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
Do not spray on an open flame or other ignition source. (P211)
Do not pierce or burn, even after use. (P251)
Avoid release to the environment. (P273)

Response

Call a POISON CENTER/doctor if you feel unwell. (P312)

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

Disposal

Dispose of contents/container in accordance with local regulation.
(P501)

Hazardous substances

cyclopentane
Hexane, branched and linear

Additional labelling

UFI: W01J-20JW-J00W-7MGR

2.3. Other hazards

Additional warnings

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
cyclopentane	CAS No.: 287-92-3 EC No.: 206-016-6 REACH: 01-2119463053-47-XXXX Index No.: 601-030-00-2	25-40%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 3, H412	
propane	CAS No.: 74-98-6 EC No.: 200-827-9 REACH: 01-2119486944-21-XXXX Index No.: 601-003-00-5	25-40%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	

ethanol;ethyl alcohol	CAS No.: 64-17-5 EC No.: 200-578-6 REACH: 01-2119457610-43-XXXX Index No.: 603-002-00-5	15-25%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 (SCL: 50.00 %)
Hexane, branched and linear	CAS No.: 92112-69-1 EC No.: 295-570-2 REACH: Index No.:	5-10%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411
Tricyclo[3.3.1.13,7]decane	CAS No.: 281-23-2 EC No.: 206-001-4 REACH: 01-2120041464-63-XXXX Index No.:	5-10%	Aquatic Acute 1, H400 (M=1)

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

IF INHALED: Move to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or a doctor.

Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person.
In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container. In a fire or if heated, a pressure increase will occur and the container may burst.
In use may form flammable/explosive vapour-air mixture.
Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:
Carbon oxides (CO / CO2)

5.3. Advice for firefighters

To avoid contact with the substance, wear self-contained breathing apparatus and protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Accidental releases always pose a serious risk of fire or explosion.
Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.
Ensure adequate ventilation, especially in confined areas.
Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 “Disposal considerations” on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Because of the danger of self-ignition, any waste from the product, spray mist and soiled rags etc. are to be kept in a fire-proof place in air-tight containers, alternatively the waste is to be burned.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.
Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.
Joint storage is permitted for products in storage classes: 2B, 3, 6.1A, 6.1B, 6.1C, 6.1D, 8A, 8B, 10, 11, 12, 13
Restrictions apply to joint storage of products in storage class: 5.1C
Joint storage is NOT allowed for products in all other storage classes.

Recommended storage material

Keep only in original packaging.

Storage class

Storage class 2 B (Aerosol packages).
TRGS 510 - Storage of hazardous substances in non-stationary containers.

Storage conditions

< 50°C

Incompatible materials

Strong oxidizing agents

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propane
Long term exposure limit (8 hours) (ppm): 1000
Long term exposure limit (8 hours) (mg/m³): 1800
Short term exposure limit (15 minutes) (ppm): 4000
Short term exposure limit (15 minutes) (mg/m³): 7200
Category for short-term values: II
Annotations:
DFG = Senate Commission for the examination of Harmful working materials of the DFG (MAK Commission)

ethanol;ethyl alcohol
Long term exposure limit (8 hours) (ppm): 200
Long term exposure limit (8 hours) (mg/m³): 380
Short term exposure limit (15 minutes) (ppm): 800
Short term exposure limit (15 minutes) (mg/m³): 1520
Category for short-term values: II
Annotations:
DFG = Senate Commission for the examination of Harmful working materials of the DFG (MAK Commission)
Y = No risk of fetal damage is to be feared if the occupational exposure limit (OEL) value and the biological limit value (BLV) are adhered to.

Technical requirements for hazardous substances, workplace exposure limits, TRGS 900 (Jan. 2006)

DNEL

cyclopentane

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	214 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	432 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	643 mg/m³
Long term – Systemic effects - Workers	Inhalation	3000 mg/m³
Long term – Systemic effects - General population	Oral	214 mg/kg bw/day

ethanol;ethyl alcohol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	206 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	343 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	114 mg/m³
Long term – Systemic effects - Workers	Inhalation	380 mg/m³
Short term – Local effects - General population	Inhalation	950 mg/m³

Short term – Local effects - Workers	Inhalation	1900 mg/m³
Long term – Systemic effects - General population	Oral	87 mg/kg bw/day

PNEC

ethanol;ethyl alcohol

Route of exposure:	**Duration of Exposure:**	**PNEC:**
Freshwater		960 µg/L
Freshwater sediment		3.6 mg/kg
Intermittent release (freshwater)		2.75 mg/L
Marine water		790 µg/L
Marine water sediment		2.9 mg/kg
Predators		380-720 mg/kg
Sewage treatment plant		580 mg/L
Soil		630 µg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

Provide adequate general and local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

Type	**Class**	**Colour**	**Standards**	
AX		Brown	EN14387	
Combination filter A2B2E2K1-P2	Class 1/2	Brown/Gray/Yellow/Green/White	EN14387	

Skin protection

Recommended	**Type/Category**	**Standards**	
Dedicated work clothing should be worn.	-	-	

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Butyl	0,7	> 240	EN374-2, EN16523-1, EN388, EN421	

Eye protection

Type	Standards	
Face shield alternatively safety glasses with side shields.	EN166	
Face shield	EN 166 / EN ISO 16321-1	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state
Aerosol

Colour
Colourless

Odour / Odour threshold
Characteristic

pH
No data available.

Density (g/cm^3)
No data available.

Kinematic viscosity
No data available.

Particle characteristics
No data available.

Phase changes

Melting point/Freezing point (°C)
No data available.

Softening point/range (°C)
Does not apply to aerosols.

Boiling point (°C)
No data available.

Vapour pressure
No data available.

Relative vapour density
No data available.

Decomposition temperature (°C)
No data available.

Data on fire and explosion hazards

Flash point (°C)
-87.0 @ 1.013 hPa

Flammability (°C)
The material is ignitable (264 °C).

Auto-ignition temperature (°C)

No data available.

Lower and upper explosion limit (% v/v)

0.6 - 15

Solubility

Solubility in water

No data available.

n-octanol/water coefficient (LogKow)

No data available.

Solubility in fat (g/L)

No data available.

9.2. Other information

VOC (g/L)

600

Other physical and chemical parameters

No data available.

Oxidizing properties

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 “Handling and storage”.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure
May cause drowsiness or dizziness.

STOT-repeated exposure
Based on available data, the classification criteria are not met.

Aspiration hazard
Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics
Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

11.2. Information on other hazards

Endocrine disrupting properties
This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information
None known.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	cyclopentane
Species:	Fish
Duration:	96 hours
Test:	LL50
Result:	29.3 mg/L

Product/substance	propane
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	27,98 mg/L

Product/substance	propane
Species:	Algae
Duration:	96 hours
Test:	EC50
Result:	7,71 mg/L

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Product/substance	cyclopentane
Result:	0% 28d
Conclusion:	-

Product/substance	ethanol;ethyl alcohol
Result:	69% 5d
Conclusion:	-

12.3. Bioaccumulative potential

Product/substance	cyclopentane
BCF:	70,8
LogKow:	3 (pH: 7, 25 °C)
Conclusion:	-

Product/substance	propane

LogKow:	1,09 (pH: 7, 20 °C)
Conclusion:	-

Product/substance	ethanol;ethyl alcohol
LogKow:	-0,77
Conclusion:	-

Product/substance	Tricyclo[3.3.1.13,7]decane
LogKow:	4,24
Conclusion:	-

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.
This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)
HP 3 - Flammable
HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 14 – Ecotoxic
Dispose of contents/container to an approved waste disposal plant.
Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

16 05 04* Gases in pressure containers (including halons) containing dangerous substances

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID ***	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR/ADN/RID	UN1950	AEROSOLS, flammable	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L Tunnel restriction code: (D) See below for additional information.
IMDG	UN1950	AEROSOLS, flammable	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L EmS: F-D S-U See below for additional information.

	14.1 UN / ID ***	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
IATA	UN1950	AEROSOLS, flammable	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	See below for additional information.

* Packing group
** Environmental hazards
*** UN number or ID number

Additional information

This product is within scope of the regulations of transport of dangerous goods.
ADR/ADN/RID / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.
IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

The product must not be used professionally by persons under 18 years of age.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)

REACH, Annex XVII

cyclopentane is subject to REACH restrictions (entry 40).
propane is subject to REACH restrictions (entry 40).
ethanol;ethyl alcohol is subject to REACH restrictions (entry 40).
Hexane, branched and linear is subject to REACH restrictions (entry 40).

WGK classification

WGK class: WGK 2

Additional information

Not applicable.

Sources

Law on the protection of mothers at work, in training and in studies (Mutterschutzgesetz - MuSchG) 23.05.2017 (BGBl. I S. 1228).
The Aerosol Packaging Ordinance of September 27, 2002 (BGBI. I p. 3777, 3805), amended with the thirteenth Ordinance on the Product Safety Act (Aerosol Packaging Ordinance) (13th ProdSV) of November 8, 2011 (BGBl. L p. 2178).
Twelfth ordinance for the implementation of the Federal Immission Control Act (Major Accidents Ordinance - 12th BImSchV).
Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV).
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H220, Extremely flammable gas.
H225, Highly flammable liquid and vapour.
H280, Contains gas under pressure; may explode if heated.
H304, May be fatal if swallowed and enters airways.
H315, Causes skin irritation.
H319, Causes serious eye irritation.
H336, May cause drowsiness or dizziness.
H400, Very toxic to aquatic life.
H411, Toxic to aquatic life with long lasting effects.
H412, Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EC = Effective concentration
ED = Effective dose
EINECS = European Inventory of Existing Commercial chemical Substances
EL = Effective Loading
ErC = Concentration associated with x% growth rate response
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
HP = Hazardous Property code
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IC = X maximum inhibitory concentration
IMDG = International Maritime Dangerous Goods
LC = Lethal concentration
LCLo = Value is the lowest concentration of a material in air reported to have caused the death of animals or humans
LD = Lethal dose
LOAEC = Lowest Observed Adverse Effect Concentration
LOAEL = Lowest Observed Adverse Effect Level
LOEC = Lowest Observed Effect Concentration
LogKow = logarithm of the n-octanol/water coefficient
LL = Lethal Loading
M = For multiplication factor

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NOAEC = No Observed Adverse Effect Concentration
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
NOELR = No Observable Effect Loading Rate
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVCB = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).
The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).
The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

Max Liese

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
Country-language: DE-en